رى - SEE BASE TERMINATION DETAIL FOR PERIMETER SECUREMENT OPTIONS SEALANT (IF REQUIRED BY THE SPECIFIC SYSTEM) -EXPANDING SHANK FASTENERS (APPROX. 12" [305mm] O.C., DEPENDING UPON WIND ZONE AND LOCAL CONDITIONS) -EXIST. ROOF DECK EXIST. INSULATION SPECIFIED RECOVERY BOARD (ADHERED TO WALL) TERMINATION BAR POLYURETHANE SEALANT SHEET METAL COUNTERFLASHING (SEE TABLE 2) OPTIONAL: 2" [51mm] WIDE CLIP APPROX. 30" [762mm] O.C. INSTALL POLYURETHANE SEALANT AND TOOL TO FACILITATE WATER RUN-OFF WATERPROOF AS REQUIRED SPECIFIED SINGLE PLY ROOF MEMBRANE 3" [76mm] LAP AT JOINTS EXIST. ROOF MEMBRANE



THIS DETAIL SHOULD BE USED ONLY WHERE THE DECK IS SUPPORTED BY THE WALL.
TOP LAYER OF INSULATION CAN BE EITHER THERMAL INSULATION OR COVERBOARD INSULATION.



SURFACE MOUNTED COUNTERFLASHING

PROJECT TITLE:

ROOF RECOVERY

2014

	JIILLI
	エコヨロン
	CAD FILE
8/7/2014	DATE
	SCALE
	CHECKED
	DRAWN BY:
	JOB NO,

DRAWING NO.

d002